



SEA POWER THINNERS

PRODUCT DESCRIPTION

SEA POWER THINNERS are volatile virgin solvents used to dilute or extend oil-based paints or cleanup after usages. They include properties for easy usage and can aid in paint removal on brushes, rollers and general cleanup of spills or splatters. See Product List to match the type of thinner to use on specific surface grains or textures for sufficient and proper use.

APPLICATION GUIDE

- | | |
|---------------------------|---|
| 1. RECOMMENDED USE: | Interior & Exterior application |
| 2. PRODUCT DESCRIPTION: | Solvent based |
| 3. APPEARANCE: | Transparent colours |
| 4. CONSISTANCY: | Ready to Use & concentrate |
| 5. METHOD OF APPLICATION: | By ragging with a muslin cloth |
| 6. RECOATING TIME: | 5 minutes |
| 7. SHELF LIFE: | 1 year in unopened condition |
| 8. COVERING: | 75-100 sq.ft/coat/Lt depending on surface |
| 9. PACKAGING: | 500ml, 1L, 5 Ltrs, 20 Ltrs |

PERFORMANCE

1. Excellent solubility in Solvent base paints.
2. Enhances the beauty of natural wood grain
3. Controlled penetration with fade resistant color
4. Fast Drying
5. Lead free

NOTES

1. Always make a sample test before you start with the project by applying the stain on a small piece of wood to verify the desired color.
2. Stir the contents very well before use.
3. Use rubber gloves to protect your hands from stains.
4. To ensure your top coat adheres properly, wipe of excess stain that didn't penetrate the surface properly, following the direction of the grain.
5. While mixing, measure the proportions carefully to produce the same dilution if mixing is to be repeated.
6. Recoating time depends on the climatic conditions.
7. Coverage depends on the porosity of the surface.

SAFETY MEASURES

1. Store the product in ambient conditions in well-ventilated location and away from source of ignition and fuel.
2. Use rubber/polyurethane gloves, safety goggles/glasses and safety masks while handling paint.
3. Do not inhale or ingest. In case of inhalation, move to fresh air and seek medical attention if symptoms persist.
4. Do not dispose in any drain or water ways.
5. Avoid eye and skin contact.
6. Product is flammable.